GRAPHITE MODULAR 65MM THICK



PRODUCT RANGE

CLAY PAVING BRICK PA-PAVING CLASS A

Units that are selected or produced for their durability and for a high degree of uniformity in size and shape.

Variations in colour, texture, and size are natural characteristics of clay products and production variations can occur from batch to batch. Whilst every effort is made to provide brochures consistent with products delivered to site, they should be viewed as a guide only.

GRAPHITE MODULAR 65MM THICK



SPECIFICATIONS

Size (length x width x thickness)	220 x 98.5 x 65mm	Average Mass Per Paver	2.8kg
Nibbed	If ticked, yes	Pavers Per Pallet	500
Chamfered	If ticked, yes	Typical 24 Hour Water Absorption	>4%
Factory Manufactured At	Springs, Gauteng	Exposure Zone Suitability]-4
Pavers per m ² (Excl cutting & watse)	48	Traffic	Medium Traffic
SANS		Dish Drain Channel	If ticked, yes
ISO	9001:2015	Kerb End	If ticked, yes
Average Compressive Strength	>78MPa	Bulinose on Flat	If ticked, yes
Average Modulus of Rupture	>6MPa	Moisture Expansion Category	Category I



- www.corobrik.co.za



Menlyn Learning Hub

Download the high-resolution swatches, BIM files and view more project photos | www.corobrik.co.za

Variations in colour, texture, and size are natural characteristics of clay products and production variations can occur from batch to batch. Whilst every effort is made to provide brochures consistent with products delivered to site, they should be viewed as a guide only.