

DE HOOP MULTIBLEND MODULAR 73MM THICK



PRODUCT RANGE
CLASSIFICATION

CLAY PAVING BRICK
PB-PAVING CLASS B

Clay pavers that are selected or produced for their durability and for their uniformity in size and shape.



Variations in colour, texture, and size are natural characteristics of clay products and production variations can occur from batch to batch. Whilst every effort is made to provide brochures consistent with products delivered to site, they should be viewed as a guide only.

DE HOOP MULTIBLEND MODULAR 73MM THICK



SPECIFICATIONS

Size (length x width x thickness)	220 x 100 x 73mm	Average Mass Per Paver	3.2kg
Nibbed	<input type="checkbox"/> If ticked, yes	Pavers Per Pallet	500
Chamfered	<input type="checkbox"/> If ticked, yes	Typical 24 Hour Water Absorption	>4%
Factory Manufactured At	De Hoop, Western Cape	Exposure Zone Suitability	1
Pavers per m² (Excl cutting & waste)	48	Traffic	Light-Medium Traffic
SANS	-	Dish Drain Channel	<input type="checkbox"/> If ticked, yes
ISO	-	Kerb End	<input type="checkbox"/> If ticked, yes
Average Compressive Strength	>49MPa	Bullnose on Flat	<input type="checkbox"/> If ticked, yes
Average Modulus of Rupture	>3MPa		



www.corobrik.co.za

Download the high-resolution swatches, BIM files and view more project photos | www.corobrik.co.za

Variations in colour, texture, and size are natural characteristics of clay products and production variations can occur from batch to batch. Whilst every effort is made to provide brochures consistent with products delivered to site, they should be viewed as a guide only.