

# NUTMEG COBBLE



**PRODUCT RANGE**  
**CLASSIFICATION**

**CLAY PAVING BRICK**  
**PA-PAVING CLASS A**

Units that are selected or produced for their durability and for a high degree of uniformity in size and shape.



Variations in colour, texture, and size are natural characteristics of clay products and production variations can occur from batch to batch. Whilst every effort is made to provide brochures consistent with products delivered to site, they should be viewed as a guide only.

# NUTMEG COBBLE



## SPECIFICATIONS

<b>Size</b> (length x width x thickness)	108.5 x 108.5 x 50mm	<b>Average Mass Per Paver</b>	1.2kg
<b>Nibbed</b>	<input type="checkbox"/> If ticked, yes	<b>Pavers Per Pallet</b>	864
<b>Chamfered</b>	<input checked="" type="checkbox"/> If ticked, yes	<b>Typical 24 Hour Water Absorption</b>	>3%
<b>Factory Manufactured At</b>	Springs, Gauteng	<b>Exposure Zone Suitability</b>	1-4
<b>Pavers per m<sup>2</sup></b> (Excl cutting & waste)	80	<b>Traffic</b>	Light Traffic
<b>SANS</b>	-	<b>Dish Drain Channel</b>	<input type="checkbox"/> If ticked, yes
<b>ISO</b>	9001:2015	<b>Kerb End</b>	<input type="checkbox"/> If ticked, yes
<b>Average Compressive Strength</b>	>48MPa	<b>Bullnose on Flat</b>	<input type="checkbox"/> If ticked, yes
<b>Average Modulus of Rupture</b>	>5MPa	<b>Moisture Expansion Category</b>	Category II



[www.corobrik.co.za](http://www.corobrik.co.za)

## THE NUTMEG RANGE



Download the high-resolution swatches, BIM files and view more project photos | [www.corobrik.co.za](http://www.corobrik.co.za)

Variations in colour, texture, and size are natural characteristics of clay products and production variations can occur from batch to batch. Whilst every effort is made to provide brochures consistent with products delivered to site, they should be viewed as a guide only.