

NOUGAT MODULAR 50MM THICK



PRODUCT RANGE
CLASSIFICATION

CLAY PAVING BRICK
PA - PAVING CLASS A

Units that are selected or produced for their durability and for a high degree of uniformity in size and shape.



Variations in colour, texture, and size are natural characteristics of clay products and production variations can occur from batch to batch. Whilst every effort is made to provide brochures consistent with products delivered to site, they should be viewed as a guide only.

NOUGAT MODULAR 50MM THICK



SPECIFICATIONS

Size (length x width x thickness)	220 x 108.5 x 50mm	Average Mass Per Paver	2.6kg
Nibbed	<input type="checkbox"/> If ticked, yes	Pavers Per Pallet	500
Chamfered	<input type="checkbox"/> If ticked, yes	Typical 24 Hour Water Absorption	TBC
Factory Manufactured At	Springs, Gauteng	Exposure Zone Suitability	TBC
Pavers per m² (Excl cutting & waste)	41	Traffic	Light Traffic
SANS	-	Dish Drain Channel	<input type="checkbox"/> If ticked, yes
ISO	9001:2015	Kerb End	<input type="checkbox"/> If ticked, yes
Average Compressive Strength	TBC	Bullnose on Flat	<input type="checkbox"/> If ticked, yes
Average Modulus of Rupture	TBC	Moisture Expansion Category	Category I



www.corobrik.co.za

Download the high-resolution swatches, BIM files and view more project photos | www.corobrik.co.za

Variations in colour, texture, and size are natural characteristics of clay products and production variations can occur from batch to batch. Whilst every effort is made to provide brochures consistent with products delivered to site, they should be viewed as a guide only.