CHAMPAGNE COBBLE



PRODUCT RANGE CLASSIFICATION

CLAY PAVING BRICK PA-PAVING CLASS A

Units that are selected or produced for their durability and for a high degree of uniformity in size and shape.



Following The South African National Standard (SANS 1575:2007) for burnt clay paving units.



Variations in colour, texture, and size are natural characteristics of clay products and production variations can occur from batch to batch. Whilst every effort is made to provide brochures consistent with products delivered to site, they should be viewed as a guide only.

CHAMPAGNE COBBLE



SPECIFICATIONS

Size (length x width x thickness)	108.5 x 108.5 x 50mm	Average Mass Per Paver	1.2kg
Nibbed	If ticked, yes	Pavers Per Pallet	864
Chamfered	If ticked, yes	Typical 24 Hour Water Absorption	>8%
Factory Manufactured At	Springs, Gauteng	Exposure Zone Suitability	1-3
Pavers per m ² (Excl cutting & watse)	80	Traffic	Light Traffic
SANS	*	Dish Drain Channel	If ticked, yes
ISO	9001:2015	Kerb End	If ticked, yes
Average Compressive Strength	>50MPa	Bullnose on Flat	If ticked, yes
Average Modulus of Rupture	>4MPa	Moisture Expansion Category	Category II



www.corobrik.co.za



Download the high-resolution swatches, BIM files and view more project photos | www.corobrik.co.za

Variations in colour, texture, and size are natural characteristics of clay products and production variations can occur from batch to batch. Whilst every effort is made to provide brochures consistent with products delivered to site, they should be viewed as a guide only.

Information correct as at 2022/01/26 www.corobrik.co.za