



## CLAY FACE BRICK RANGE Special Shaped Bricks

Denotes normally exposed face

#### Stock Special Shape Bricks








Double Bullnose



Single Cant



Double Cant



Solid

#### Made to Order



Single Bullnose Solid



**Double Bullnose Solid** 




**Bullnose Header** on Flat




Squint 30°/45°/60°



Single Cant Solid




**Double Cant Solid** 




Plinth Header Solid




Plinth Stretcher



Plinth Stretcher Solid




Sill Brick I




Sill Brick II

#### **Purpose Made Specials**




**Bullnose Stretcher** on Flat



Internal Angle 45°



**Bullnose Double** Header on Flat




Plinth External Return



**Bullnose Double** Stretcher on Flat




Concave Header



**Bullnose on End** (Cownose)



**Concave Stretcher** 



External Angle 45°




Plinth Header

# **CLAY FACE BRICK**

### **Dimensions**


#### Single Bullnose

- A 222mm
- B 106mm
- C 73mm
- R 53mm




#### Single Bullnose Solid

- A 222mm
- B 106mm
- C 73mm
- R 53mm




#### **Double Bullnose**

- A 222mm
- B 106mm
- C 73mm
- R 53mm




#### **Double Bullnose Solid**

- A 222mm
- B 106mm
- C 73mm
- R 53mm




#### **Bullnose Header** on Flat

- A 222mm
- B 106mm C 73mm
- R 53mm




#### **Bullnose Stretcher** on Flat

- A 222mm
- B 106mm
- 73mm
- R 53mm




#### **Bullnose Double Header** on Flat

- A 222mm
- B 106mm
- C 73mm
- R 53mm




#### **Bullnose Double** Stretcher on Flat

- A 222mm
- B 106mm
- C 73mm
- R 53mm




#### **Bullnose on End** (Cownose)

- A 222mm
- B 106mm
- C 73mm
- R 53mm



#### Squint

|   | 30°   | 45°   | 60°   |
|---|-------|-------|-------|
| Α | 169mm | 169mm | 169mm |
| В | 106mm | 106mm | 106mm |
| С | 73mm  | 73mm  | 73mm  |
| D | 53mm  | 53mm  | 53mm  |
| Ε | 169mm | 138mm | 92mm  |
| F | 92mm  | 97mm  | 120mm |




## **CLAY FACE BRICK**

### **Dimensions**


#### External Angle 45°

- A 222mm
- B 106mm
- C 73mm
- D 106mm
- E 178mm
- F 57mm




#### Internal Angle 45°

- A 130mm
- B 106mm
- 73mm
- D 13mm
- E 174mm
- F 57mm




### Single Cant

- A 222mm
- B 106mm
- C 73mm
- D 48mm
- E 164mm



#### Single Cant Solid

- A 222mm
- B 106mm
- C 73mm
- D 48mm
- E 164mm




#### **Double Cant**

- A 222mm
- B 106mm
- C 73mm
- D 48mm
- E 106mm

#### **Double Cant Solid**

- A 222mm
- B 106mm
- C 73mm
- E 106mm
- D 48mm




#### Plinth Header

- A 222mm
- B 106mm
- C 73mm
- D 15mm E 164mm


### Plinth Header Solid

- A 222mm
- B 106mm
- 73mm
- D 15mm E 164mm




#### Plinth Stretcher

- A 222mm
- B 106mm
- C 73mm
- D 15mm E 48mm



#### Plinth Stretcher Solid

- A 222mm
- B 106mm
- C 73mm
- D 15mm
- E 48mm




# CLAY FACE BRICK

## **Dimensions**


#### Plinth External Return

- A 222mm
- B 106mm
- C 73mm
- D 15mm E 164mm
- F 48mm




#### **Concave Header**

- A 48mm
- B 222mm
- C 73mm
- R 25mm




#### **Concave Stretcher**

- A 106mm
- B 222mm
- C 73mm
- R 25mm




#### Sill Brick I

- A 222mm
- B 106mm
- C 73mm
- $\mathsf{D}\ 10\mathsf{mm}$
- E 25mm
- R 50mm



#### Solid

- A 73mm
- B 106mm
- C 222mm



#### Sill Brick II

- A 222mm
- B 106mm
- C 73mm
- D 53mm
- E 111mm

