

AMBER SATIN FBS



PRODUCT RANGE CLASSIFICATION

CLAY FACE BRICK FBS - FACE BRICK STANDARD

Durable face bricks possessing a high degree of size, shape and colour uniformity.



BRICK TEXTURE - SATIN

A smooth, non-grainy face finish or slightly grainy face finish.



Variations in colour, texture, and size are natural characteristics of clay products and production variations can occur from batch to batch. Whilst every effort is made to provide brochures consistent with products delivered to site, they should be viewed as a guide only.

AMBER SATIN FBS



SPECIFICATIONS

Size (length x width x height)	222 x 106 x 73mm	Classification	FBS
SANS	-	ISO	9001:2015
Typical Compressive Strength	>19MPa	Typical 24^{hr} Water Absorbtion	>10%
Moisture Expansion Category	II	Efflorescence Rating	Nil-Slight
Exposure Zone Suitability	1 - 3	Bricks per m² (excluding cutting & waste)	51
Factory Manufactured At	Rietvlei, Gauteng	Bricks per pallet	464
Average mass per brick	2.2kg	Available in Special Shaped Bricks	No



www.corobrik.co.za



Home in Sondela Nature Reserve | Architect – 86 red BRICKS Architects

[Download the high-resolution swatches, BIM files and view more project photos | www.corobrik.co.za](http://www.corobrik.co.za)

Variations in colour, texture, and size are natural characteristics of clay products and production variations can occur from batch to batch. Whilst every effort is made to provide brochures consistent with products delivered to site, they should be viewed as a guide only.