
Buff Satin
FBS

CLASSIFICATION	FBS
TEXTURE	Bricks with a flat and even surface, providing a clean look with minimal texture.

Choose clay face bricks for their unmatched durability, timeless beauty, and excellent thermal insulation, all while requiring no maintenance, ensuring your building stands the test of time with minimal effort.




Variations in colour, texture, and size are natural characteristics of clay products and production variations can occur from batch to batch. Whilst every effort is made to provide brochures consistent with products delivered to site, they should be viewed as a guide only.

Buff Satin FBS

SPECIFICATIONS

Size (length x width x height)	222 x 106 x 73mm	**Classification**	FBS
SANS	227:2007	**ISO**	'-
Typical Compressive Strength	>25 MPa	**Typical 24^{hr} Water Absorbtion**	>10%
Moisture Expansion Category	I	**Efflorescence Rating**	Nil
Expoure Zone Suitability	02-01	**Bricks per m^2** (excluding cutting & waste)	51
Factory Manufactured At	Rosema, Gauteng	**Bricks per pallet**	480
Average mass per brick	2.6kg	**Available in Special Shaped Bricks**	Yes



Download the high-resolution swatches, BIM files and view more project photos | www.corobrik.co.za

Variations in colour, texture, and size are natural characteristics of clay products and production variations can occur from batch to batch. Whilst every effort is made to provide brochures consistent with products delivered to site, they should be viewed as a guide only.

For image and project credits, please visit: www.corobrik.co.za/featured-projects

Information correct as at 28/06/2024